

# Technical Information Sheet



## EcoWhite™ 12" QuickSeam™ Flashing

Item Description	Item Number
12" (304 mm) x 50' (15.2 m) Roll	W56RACEW12

### Description

Elevate EcoWhite EPDM 12" (304 mm) QuickSeam Flashing consists of semi-cured Flashing factory laminated to cured QuickSeam Tape. It is designed to flash inside and outside corners, pipes, penetration pockets and other applications as required by Elevate Specifications and Details. It is available in 12" (304 mm) wide by 50' (15.2 m) long rolls.

### Method of Application

1. Use Single-Ply QuickPrime™ Primer or Single-Ply QuickPrime™ LVOC Primer applied with a QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime mating surfaces. Refer to Elevate Installation Instruction Sheet for QuickSeam Flashing (included in each carton) and Elevate Specifications and Details.
2. When cloudy conditions below 60 °F (15.6 °C) occur, use heat guns (without ignition sources) to heat EcoWhite EPDM QuickSeam Flashing. This will ensure good formability of the QuickSeam Flashing to the primed substrate.
3. On sunny days less than 70 °F (21.1 °C), place EcoWhite EPDM QuickSeam Flashing on roof (prior to application) with flashing side up to allow QuickSeam FormFlash to warm to ensure good formability.
4. On sunny days greater than 70 °F (21.1 °C), place EcoWhite EPDM QuickSeam Flashing on roof (prior to application) with release paper side up to prevent QuickSeam Flashing from gaining too much heat and to ensure good formability.
5. Refer to application instructions at Elevate Technical Database, [www.HolcimElevate.com](http://www.HolcimElevate.com)

### Storage

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (37.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

## Shelf Life

Shelf life of 6 months can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C). Shelf life will be shortened if exposed to elevated temperatures.

## Precautions

- Refer to Safety Data Sheets (SDS) for additional safety information.
- EcoWhite EPDM QuickSeam Flashing is semi-cured. DO NOT STRETCH.

## LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Michigan Center, MI

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Physical Properties			
QuickSeam Tape	Value	EPDM Flashing	Value
Base	Rubber Polymer	Base	EPDM
Color	White	Color	White
Solvents	None	Solvents	None
Solids	100%	Solids	100%
Cured State	Cured	Cured State	Uncured
Thickness	0.025" (0.635 mm) ± 0.007" (0.18 mm)	Thickness	0.060" (1.6 mm) ± 0.005" (0.13 mm)
Width	12 ¼"	Width	12"

Packaging			
Item	Size	Carton	Pallet
Roll	12" (304 mm) x 50' (15.2 m)	1 Roll per Carton	36 Cartons per Pallet
<b>NOTE:</b> QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.			

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.