

Technical Information Sheet



EcoWhite™ QuickSeam™ Joint Cover

| Item Description | Item Number |
|---|-------------|
| White: 5.75" \pm 0.125" diameter (146 mm \pm 3.17 mm) | W56RACEWJC |

Description

Elevate™ EcoWhite QuickSeam Joint Cover is an uncured, white EPDM flashing laminated to white QuickSeam Tape. A second 3" (76 mm) diameter layer of uncured, flowing tape is applied at the center. The EcoWhite EPDM QuickSeam Joint Cover conforms to irregular surfaces such as encountered at single-ply membrane "T" joints, readily providing an excellent seal.

EcoWhite QuickSeam Joint Covers are designed to cover and seal:

- T- Joints formed by field seam intersections.
- T- Joints formed by the installation of pre-fabricated pipe flashings over field or factory seams.
- As a protection pad under sheet metal joints for EdgeGard™ or snap-on metals.

Method of Application

1. Clean the EcoWhite EPDM membrane to receive EcoWhite QuickSeam Joint Covers using Single-Ply QuickPrime™ Primer or Single-Ply QuickPrime LVOC Primer with a QuickScrubber™ or QuickScrubber Plus pad and handle to remove all dust, dirt and other contaminants that will affect the finished seam.
2. Allow to dry according to the touch-push test.
3. Additional cleaning may be required to ensure that the membrane is completely cleaned. (Caution: more cleaning is needed at factory seams.)
4. Remove the release paper from the joint cover, taking care not to touch the outside edges of the joint cover.
5. Fold the joint cover in half. Position the center of the joint cover over the target point and mate the joint cover to the prepared surface.
6. Roll the mated surface of the joint cover with a 2" (51 mm) silicone roller from the center outward working the joint cover into the step-off or irregularity.
7. Install Seam Edge Treatment per Holcim Specifications and Details.
8. Refer to application instructions for specifics: www.HolcimElevate.com

Storage

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (38 °C).
- When exposed to lower temperatures, restore to room temperature prior to use.

Shelf Life

- Shelf life of 6 months can be expected when stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Precautions

Refer to Safety Data Sheets (SDS) for additional safety information.

Packaging

100 per carton, 60 cartons per pallet

LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Prescott, AR / Michigan Center, MI

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

| Typical Properties | |
|--------------------------|---|
| Property: QuickSeam Tape | Value |
| Base | Rubber Polymers |
| Color | White |
| Solvents | None |
| Solids | 100% |
| Cured State: | |
| Splice Tape | Cured |
| Center Tape | Uncured and flowable |
| Thickness: | |
| Splice Tape | 0.030" (0.77 mm) ± 0.005" (0.13 m) |
| Center Layer | 0.037" (0.94 mm) ± 0.005" (0.13 mm) |
| Property: EPDM Flashing | Value |
| Material | Semi-cured flashing, conforming to ASTM 4811 minimum specifications |
| Color | White |
| Size | 5.75" ± 0.125" diameter (146 mm ± 3.17 mm) |
| Thickness | 0.060" ± 0.005"q (1.5 mm ± .13 mm) |

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.