

Technical Information Sheet



QuickScrubber™ Kit

Item Description	
30 Scrub Pads and 4 Holders	

Item Number W563582045

Description

The Elevate QuickScrubber Kit consists of a scrub pad and holder that allows application of primers. The QuickScrubber scrub pad is secured in place to the bottom of the holder. The pads for the QuickScrubber Kit are included with each kit.

The bottom-bearing surface of the QuickScrubber holder is slightly arched. When proper pressure is applied in a back-and-forth motion, the holder flattens and assures that proper contact is maintained.

Method of Application

- 1. Install a QuickScrubber pad on the bottom of the handle by pressing the pad onto the industrial-grade gripping surface with firm hand pressure.
- 2. Wet the pads with the primer. Primer must be applied on all surfaces to receive QuickSeamTM tapes.
- 3. Use back and forth strokes with heavy pressure along the length of the splicing area, until membrane surfaces become dark gray in color with no streaking or puddling.
- 4. Bear down on the QuickScrubber pad during application to ensure the total surface is in contact with the priming surface.

Storage

Keep pads clean and dry prior to use.

Coverage Rate

Each pad will prime approximately 100 - 200 linear feet (30 - 61 m) with a width of 6" - 7" (152.4 mm - 177.8 mm). Change pads routinely. Do not attempt to turn pads over and re-use. Discard after 100 - 200 feet (30 - 61 m) of priming.

August 29, 2024

Sales: (800) 428-4442 | Technical (800) 428-4511





Typical Properties

Value
High Quality Plastic
Tan
Industrial Grade Gripping Surface
Value
Nylon fibers with abrasive grain bound with solvent resistant resins
3" (76.2 mm) x 6" (152.4 mm) x 0.25" (6.4 mm)
Maroon
220 - 240
35 oz. (993 gm)/ yd ²

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.

August 29, 2024

Sales: (800) 428-4442 | Technical (800) 428-4511

